



NEW



WhisperCut PLUS

Application:

For tear free jointing with feed and against feed (e.g. jump cutting).

Machine:

Edge processing machines and double end tenoners.

Workpiece material:

Particle- and fibre materials (MDF etc.) uncoated, veneered, plastic- and paper coated.

Technical information:

Tool with alternate shear angle for tear free jointing edge and jointed edge. Low noise design with noise reduction up to 5dB (A) and very efficient chip clearance (> 95%). 3,1 mm resharpening area. Knives are sharpened in installed state for maximum processing quality. Diamond knives are compatible with the WhisperCut.

Note:

When mounting the Diamond knives with 3,1 mm resharpening area, the 5 mm diameter of the WhisperCut increases due to increased resharpening area.

Diamaster WhisperCut PLUS - DFC, LowNoise

WM 230-2-02

Maschine	D	SB	ND	BO	NAL	n _{max.}	Z	Typ	ID	ID
	mm	mm	mm	mm		min ⁻¹			LL	RL
Homag, IMA	180	34	34	35	DKN 2	9500	6x3	AS	192173	• 192174 •
Homag, IMA	180	43	46	35	DKN 1	9500	6x4	AS	192175	• 192176 •
Homag, IMA	180	63	46	35	DKN 3	9500	6x6	AS	192177	• 192178 •
Homag, IMA	180	34	34	35	DKN 2	9500	8x3	AS	192179	• 192180 •
Homag, IMA	180	43	46	35	DKN 1	9500	8x4	AS	192181	• 192182 •
Homag, IMA	180	63	46	35	DKN 3	9500	8x6	AS	192183	• 192184 •